

SAFETY DATA SHEET

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations.

SECTION 1: PRODUCT AND COMPANY INDENTIFICATION

Name of the Product: GroundTack
Product Form: Mixture

Recommended Use: No use is specified Company: Staticworx

706 Waterbury Stowe Road Waterbury Center, VT 05677

Telephone Number for Information (617) 923-2000

Emergency Phone Number 800-255-3924 or Local Poison Control Center

SECTION 2: HAZARD(S) IDENTIFICATION

Classification (GHS-US): Not classified

Label Elements: GHS-US Labeling: No labeling applicable

Hazard Statement: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US): Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS#	% (w/w)
Vinyl Ester Acrylic Acid Acrylonitrile Co-polymer	27233-89-2	40 - 70
Water	7732-18-5	30 - 60
Cellulose*	9004-34-6	1 - 5

^{*}This product contains a material that may be hazardous when present as an airborne dust. Since this product is in a liquid form, the material is not able to become airborne and cannot be inhaled. Thus, the hazards usually associated with this material are not applicable to this product.

SECTION 4: FIRST AID MEASURES

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show

the label if possible).

Skin Contact: Rinse immediately with plenty of water. Remove contaminated clothing. Rinse affected area with

water for at least five minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least five minutes. Remove contact lenses if easy to do. Continue

rinsing. Obtain medical attention if redness, pain, or irritation occurs.

Ingestion:Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.Inhalation:Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention

if breathing difficulty persists.

Most Important Symptoms and Effects Both Acute and Delayed

General: Not expected to present a significant hazard under anticipated conditions of normal use.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: Prolonged exposure to liquid may cause a mild irritation. Ingestion: Ingestion is likely to be harmful or have adverse effects.

Inhalation:Prolonged exposure may cause irritation.Chronic Symptoms:None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.



Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: None known.

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).

For Non-Emergency Personnel: Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel: Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Ventilate area.

Environmental Precautions: Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods For Cleaning Up: Clean up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities

after a spill.

Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Reference to Other Sections: See Heading 8. Exposure controls and personal protection. For further information refer to Section 13.

SECRION 7: HANDLING AND STORAGE

Precautions for Safe Handling: Handle in accordance with appropriate industrial hygiene and safety procedures. Wash hands and

other exposed areas with mild soap and water before eating, drinking, or smoking and when leaving

work.

Technical Measures: Comply with applicable regulations.

Proper Storage: Store in a dry, cool, and well-ventilated place. Keep container closed when not in use. Keep/store away

from direct sunlight, extremely high or low temperatures, and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s) No use is specified.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control Parameters

For substances listed in Section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency, including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Cellulose (9004-34-6)

USA ACGIH TWA (mg/m³) 10 mg/m³

USA OSHA OSHA PEL (TWA) (mg/m³) 15 mg/m³ (total dust) 5 mg/m³

(respirable fraction)

USA NIOSH NIOSH REL (TWA) (mg/m³) 10 mg/m³ (total dust) 5 mg/m³ (respirable dust)

Alberta OEL TWA (mg/m³) 10 mg/m³

British Columbia OEL TWA (mg/m³) 10 mg/m³ (total dust) 3 mg/m³

(respirable fraction)

 Manitoba
 OEL TWA (mg/m³)
 10 mg/m³

 New Brunswick
 OEL TWA (mg/m³)
 10 mg/m³

 Newfoundland & Labrador
 OEL TWA (mg/m³)
 10 mg/m³

 Nova Scotia
 OEL TWA (mg/m³)
 10 mg/m³

Nunavut OEL TWA (mg/m³) 5 mg/m³ (respirable mass) 10 mg/m³

(total mass)



Northwest Territories OEL TWA (mg/m³) 5 mg/m³ (respirable mass) 10 mg/m³

 Ontario
 OEL TWA (mg/m³)
 10 mg/m³

 Prince Edward Island
 OEL TWA (mg/m³)
 10 mg/m³

Québec VEMP (mg/m³) 10 mg/m³ (containing no Asbestos

and <1% Crystalline silica-total dust)

 Saskatchewan
 OEL STEL (mg/m³)
 20 mg/m³

 Saskatchewan
 OEL TWA (mg/m³)
 10 mg/m³

 Yukon
 OEL STEL (mg/m³)
 20 mg/m³

Yukon OEL TWA (mg/m³) 30 mppcf 10 mg/m³

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains

and safety showers should be available in the immediate vicinity of any potential

exposure. Ensure all national/local regulations are observed.

Individual Protection Measures: Protective goggles. Gloves. Protective clothing.

Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.
Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever

exposure may exceed established Occupational Exposure Limits.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink, or smoke during use

SECTION 9: PHYSCIAL PROPERTIES

Not available **Appearance** Not available Odor **Odor Threshold** Not available **Physical State** Liquid 6.0-8.0 **Evaporation Rate** Not available **Melting Point** Not available Not available Freezing Point **Boiling Point** >100°C (212°F)

Flash Point (TCC) > 93 °C (> 200 °F) (Setaflash method)

Auto-ignition Temperature

Decomposition Temperature

Flammability (solid, gas)

Lower Flammable Limit

Upper Flammable Limit

Vapor Pressure (mmHg)

Vapor Density (air=1) Relative Vapor Density at

Not available

Not available

Not available

Not available

20 °C

Relative Density
Specific Gravity
Not available
Solubility
Not available
Viscosity
Not available
Partition Coefficient: N-Octanol/Water
Not available

Explosion Data – Sensitivity to Mechanical Impact
Explosion Data – Sensitivity to Static Discharge
Not expected to present an explosion hazard due to mechanical impact.
Not expected to present an explosion hazard due to static discharge.

VOC Content (SCAQMD Rule 1168) <1 g/L

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Stable under recommended handling and storage conditions (see Section 7).

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO2).

Hazardous Reactions: Hazardous polymerization will not occur.



SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity:

LD50 and LC50 Data:

Skin Corrosion/Irritation:

PH:

Not classified

Not classified

Not classified

Not classified

Serious Eye Damage/Irritation:

pH:
6 - 8
Respiratory or Skin Sensitization:
Not classified
Not classified
Not classified

Germ Cell Mutagenicity:

Teratogenicity:

Carcinogenicity:

Specific Target Organ Toxicity (Repeated

Not classified

Not classified

Not classified

Exposure):

Reproductive Toxicity:

Specific Target Organ Toxicity (Single Exposure):

Aspiration Hazard:

Not classified

Not classified

Not classified

Symptoms/Injuries after Inhalation: Prolonged exposure may cause irritation. Symptoms/Injuries after Skin Contact: Prolonged exposure may cause irritation. Symptoms/Injuries after Eye Contact: Prolonged exposure may cause irritation.

Symptoms/Injuries after Ingestion: Ingestion is likely to be harmful or have adverse effects. Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data: Cellulose (9004-34-6)

 LD50 Oral Rat
 > 5000 mg/kg

 LD50 Dermal Rabbit
 > 2000 mg/kg

LC50 Inhalation Rat > 5800 mg/m³ (Exposure time: 4 h)

SECTION 12: ECOLOGICAL INFORMATION

Toxicity No additional information available

Persistence and Degradability

Bioaccumulative

Mobility in Soil

Not available

Not available

Other Adverse Effects Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Methods: Dispose of waste material in accordance with all local, regional, national, provincial,

territorial, and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORTATION INFORMATION

In Accordance with DOT
In Accordance with IMDG
In Accordance with IATA
In Accordance with IATA
In Accordance with TDG
Not regulated for transport
Not regulated for transport
Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Cellulose (9004-34-6) Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations
Cellulose (9004-34-6)
U.S. - Massachusetts – Right-to-Know List

U.S. - New Jersey - Right-to-Know Hazardous Substance List



U.S. - Pennsylvania - RTK (Right-to-Know) List

Canadian Regulations Cellulose (9004-34-6) WHMIS Classification

Listed on the Canadian DSL (Domestic Substances List)
Uncontrolled product according to WHMIS classification criteria

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR), and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION

Revision Date: Other Information: 05/01/2015

This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety, and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.